



**SELF-FLASHING POLYCARBONATE SKYLIGHT - THERMALLY BROKEN WITH INSULATED CURB - Specification:**

Self-Flashing Polycarbonate dome skylights, **ORCA Manufacturing, Inc.**, Model SFP-TB - 9 ISC shall be factory assembled units, each consisting of polycarbonate domes with .072 extruded glazing sash with polyurethane thermal break to prevent condensation on interior portions of aluminum frame and with extruded aluminum glazing retaining angle. Each unit will have a built-in evaporative condensation gutter. Insulated curbs shall be of double wall construction of corrosion resistant aluminum connected at top and bottom with thermal barriers. Units shall have a 3" mounting flange for installation to roof deck. Above is of all welded construction.

NOTE: Glazing materials are NOT designed to support the weight of a person. Fall protection may be required and is available as an option.

Model:   A   x   B   SFP-TB - 9ISC, [ Glz ], [ Finish ];



**STARLIGHT  
SKYLIGHTS**

PRODUCT OF ORCA MANUFACTURING, INC

TITLE: SELF-FLASHING POLYCARBONATE,  
THERMALLY BROKEN; INSULATED CURB

Date: May 01, 2003

Drawn By AP

Sheet:  
1 of 1

Rev. By CRH

Engineer: CRH

ORCA Manufacturing, Inc.  
P.O. Box 2186  
Easton, MD 21601  
Phone: 800-776-1539